PKGVEF-30

30 kVA GRP Genset

A 30 kVA CPCB IV+ diesel genset in Pai Kane's patented GRP composite enclosure, with a VECV (Volvo Eicher) E483 engine and gull-wing service doors.



Technical specifications

Genset

Prime rating (kVA / kWe)	30 kVA / 24 kWe
Power factor	0.8
Phase and voltage	3-phase, 415 V
Frequency	50 Hz
Rated current per phase at 415 V (A)	42
Noise	Less than 75 dB(A) at 1 m
Emission norm	CPCB IV+
Model code	PKGVEF-30

Alternator

Make and model	Leroy-Somer LSAP 42.3 C
Type	Brushless, self-excited
Insulation class	Class H
Protection	IP23
Voltage regulation	±1% with 4% engine governing

Enclosure

Construction	3 mm GRP composite, acoustic foam lining (28 kg/m³)

Electrical

Controller	DEIF SGC 120 MKII
Battery (V)	12
Battery capacity	100 Ah

Engine

Make	VECV (Volvo Eicher)
Model	E483 TCIC
Gross power (bHp)	38
Cylinders	4
Aspiration	Turbocharged, intercooled
Displacement (L)	3.3
Speed (rpm)	1,500
Cooling	Liquid cooled
Governing class	Electronic, class A1

Fuel

Tank capacity (L)	90
Tank	CRCA steel, removable
Consumption at 100% load (L/h)	6.8
Consumption at 75% load (L/h)	5.3

Dimensions and weight

L × W × H (mm)	2,900 × 1,445 × 1,500
Dry weight (kg)	900

Key features

Patented GRP enclosure
A glass-reinforced plastic shell that does not rust, is UV stable and weather resistant, and insulates thermally and electrically.

Gull-wing service doors
Doors lift on gas springs to open the whole set for service.

Low vibration, super silent
Composite enclosure with acoustic foam lining; below 75 dB(A) at 1 m.

VECV E483 engine
4-cylinder, turbocharged, intercooled, 38 bHp at 1,500 rpm, 3.3 L displacement. Electronic, class A1 governing.

90 L fuel tank
Runs about 17 hours at 75% load on a full tank (5.3 L/h). CRCA steel, removable tank.

CPCB IV+ compliant
Meets India's CPCB IV+ emission norms for gensets up to 800 kW.

Power Engineering (India) Pvt. Ltd.
58/A Tuem Industrial Estate, Pernem, Goa 403512
+91 91752 22136 · sales@paikane.com · https://paikanegenerators.com/products/30-kva-grp-genset